

## METHOD FOR AMORTIZING AUTHENTICATION OVERHEAD

5  
10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

A method is disclosed for amortizing the authentication overhead of data transmissions. The method comprises establishing a first secure transmission of data between a transmitter and a receiver by transmitting at least one token to the receiver during the first secure transmission. There may be any number of senders and receivers, and any receivers may be a sender and vice versa. The method also comprises establishing at least one additional transmission of data between the sender and the receiver and transmitting the data and at least one token during the at least one additional transmission. In addition, the method compares the at least one token transmitted during the at least one additional transmission to the token transmitted during the first secure transmission to guarantee the authenticity of that at least one additional transmission.

The method may also include transmitting a preselected number of tokens during the first secure transmission. The number of additional transmissions may or may not correspond to the preselected number of tokens. The at least one additional transmission may be conducted over an unsecure connection using open

communication. The first secure transmission may be protected or encrypted.

09084012 100600